

### Overview

These vacuum cleaners are suitable to pick up dust and small deposits. It is not suitable for liquid suction. They are sturdy and powerful, simple to use with its tool kit. It is suitable for collective use, for example: hotels, schools, hospitals, factories, offices, shops etc. The equipment is HIGH HAZARD. They are used to separate all dust with all limit values of occupational exposure including carcinogenic and pathogenic.

| TECHNICAL DATA          | GS 1/33H       | GS 1/33HTC                                |
|-------------------------|----------------|---|
| Usage                   | Dry            |   |
| Motor                   | 1              |   |
| Power                   | 1000-1200W max | 1000-1200W max<br>(2600W additional plug) |
| Voltage                 | 220-240V       |   |
| Water Lift              | 2470mmH2O      |   |
| Airflow                 | 210m3/h        |   |
| Tank Capacity/Material  | 33l / Steel    |   |
| Cable Length            | 8,5m           |   |
| Filtering Surface       | 12,000cm2      |   |
| Sound Pressure Level    | 72dB[A]        |   |
| Diameter of Accessories | 38mm           | 36mm                                      |
| Dimensions (LxWxH)      | 380x380x650mm  |   |
| Weight                  | 12,0kg         |   |

### Most Frequently Used

PHARMA INDUSTRY

AGRICULTURE

CONSTRUCTION

INDUSTRY

LOGISTIC & TRANSPORT

### Exclusive Features

- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ SCREWING CONNECTION
- ▶ MICROFIBER BAG
- ▶ MULTISTAGE FILTRATION
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ H CLASS CERTIFIED
- ▶ HEPA H14 CARTRIDGE
- ▶ FILTER OVERPRESSURE INDICATORS
- ▶ SAFETY DISPOSAL SYSTEMS
- ▶ RESISTANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER



#### POWER MAX

1200  
W

#### WATER LIFT

2470  
mmH2O

#### AIRFLOW

210  
m3/h

#### TANK CAPACITY

33  
l