

### Overview

These vacuum cleaners are suitable to pick up dust and small deposits. It is not suitable for liquid suction. They are sturdy and powerful, simple to use with its tool kit. It is suitable for collective use, for example: hotels, schools, hospitals, factories, offices, shops etc. The equipment is HIGH HAZARD. They are used to separate all dust with all limit values of occupational exposure including carcinogenic and pathogenic.


TECHNICAL DATA	GS 2/62 H	GS 2/62 H TC PN
Usage	Dry	
Motor	2	
Power	2000-2400W max	2000-2400W max (1300 W additional plug)
Voltage	220-240V	
Water Lift	2470mmH2O	
Airflow	420m3/h	
Tank Capacity/Material	62l / Steel	
Cable Length	8,5m	
Filtering Surface	12,000cm2	
Sound Pressure Level	74dB[A]	
Diameter of Accessories	38mm	36mm
Dimensions (LxWxH)	550x600x960mm	
Weight	21,0kg	

### Most Frequently Used

PHARMA INDUSTRY



AGRICULTURE




CONSTRUCTION



INDUSTRY



LOGISTIC & TRANSPORT



### Exclusive Features

- ▶ STRONG HOOKS
- ▶ MICROFIBER BAG
- ▶ H CLASS CERTIFIED
- ▶ INNOVATIVE GASKET
- ▶ HEPA H14 CARTRIDGE
- ▶ MULTISTAGE FILTRATION
- ▶ SCREWING CONNECTION
- ▶ SAFETY DISPOSAL SYSTEMS
- ▶ FILTER OVER PRESSURE INDICATORS
- ▶ RESISTANT FRAMEWORK AND INLET PLUG
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ INDEPENDENT MOTORS

#### POWER MAX

2400  
W

#### WATER LIFT

2470  
mmH2O

#### AIRFLOW

420  
m3/h

#### TANK CAPACITY

62  
l